

### SKU : 131882

All machines in this series feature asymmetrical rolls. This geometry provides optimum traction even with thin metal sheets in the stretch-bending phase for high-precision bending. The rear roll is fed manually. The upper roll swivels outward for easy removal of tube-shaped bent workpieces.

- Motorized drive
- Braking motor
- Conical bender
- Hardened rollers with wire insertion grooves



## TECHNICAL SPECS

### WORKING AREA

Working length	1250 mm
Plate thickness (max.)	3 mm
Max. plate thickness for bending	2.5 mm
Bending diameter (min.)	130 mm
Roll diameter	90 mm
Roller speed	6 m/min

### DRIVE CAPACITY

Motor rating main drive	1.1 kW
-------------------------	--------

### MEASURES AND WEIGHTS

Overall dimensions (length x width x height)	2.35 m x 0.8 m x 1.13 m
Weight	570 kg

## PRODUCT DETAILS

- Asymmetrical 3-Roll Bending Machine
- Hardened rollers, suitable for stainless steel
- Adjustable bottom and rear roller
- Standard series wire core groove
- Top roller swings out with eccentric closure
- Foot switch
- Manual feed or rear roller
- Brake motor
- Supplied with conical bending feature

## STANDARD EQUIPMENT

Hardened rollers  
Conical bending feature