

Belt/Disk Sanders **KS 150 B**





TECHNICAL SPECS

WORKING AREA

45°
5.5 m/s
90°
230 mm
23.3 m/s

DRIVE CAPACITY

Motor rating main drive	0.75 kW
Supply voltage	230 V

MEASURES AND WEIGHTS

Sanding pad diameter	230 mm
Blade dimensions	150 mm x 1220 mm
Height	915 mm
Weight	50 kg

SKU:102816

The lightweight combination belt grinder with its own base has a large grinding surface with an endless grinding belt that can be used horizontally and vertically, as well as a grinding disc with an angleadjustable table in front of it. The machine is particularly suitable for roughly grinding flat, straight surfaces in order to break edges or to deburr cut edges. The grinding disc is designed for grinding outer radii or angles on narrow workpiece ends and the grinding speed can be varied over the radius of the large grinding wheel for finer processing.

- Large grinding area
- Compact design with base
- Disc grinding area with angle table
- Vertical and horizontal surface grinding

PRODUCT DETAILS

- Large sanding surface for smoothing, beveling and deburring
 Belt sander can be used horizontally and vertically
 Disk sander is ideally suited for contours, small surfaces and edges
 Support table swivels up to 45° and can be used for belt and disk sanding
 The included miter stop can be adjusted from 0° 90°
- Powerful motors and low vibrations ensure optimum sanding results

STANDARD EQUIPMENT

Adjustable stop Support table Base Grinding wheel Sanding belt Operator instructions